



MATERIAL : BODY-BRASS
 SLEEVE-BRASS
 INSULATOR-TEFLON
 CONTACT-BRASS
 C WASHER-BERYLLIUM COPPER
 FURRULE-BRASS
 CAP-BRASS

FINISH : BODY-GOLD PLATING OVER NICKEL
 SLEEVE-GOLD PLATING OVER NICKEL
 CONTACT-GOLD PLATING OVER NICKEL
 C WASHER-GOLD PLATING OVER NICKEL
 FURRULE-GOLD PLATING OVER NICKEL
 CAP-GOLD PLATING OVER NICKEL

IMPEDANCE:50 OHM
 FREQUENCY RANGE:0 TO 6.0 GHZ
 VSWR:0-4GHZ=1.2MAX(STRAIGHT)
 1.25AMX(RIGHT ANGLE)
 4-6GHZ=1.25MAX(ATRAINGT)
 1.4MAX(RAIGHT ANGLE)
 INSULATION RESISTANCE:1,000 MEGOHMS MIN

DIMENSIONS ARE IN MILLIMETERS		SCHMID-M
TOLERANCE		
· × ±0.5	ANGLE ±3°	TITLE MMCX Right Angle Plug Crimp for RG174u, RG188A/u, RG316u
· × × ±0.1		SCALE 10:1
· × × × ±0.05		REV A-0
DRAWN	DATE 90.09.11	DRAWING NO MMCX-1106-TGG
APPROVAL	DATE	FILE NO