Revisions

Revisions B; B-1; B-2..... On behalf of official Drawing.
Revisions 1; 2; 3; 4..... On behalf of experiment's Drawing.

ISS	Symbol	Description	Date
B	B	CHE for New Drawing Frame & New PN System	2006/07/11

*Change new drawing frame in Blue Color since 2009/07/01 , to comply with Company CIS Policy.

Outline Drawing

Note :

1. Single Crimp: Providing Recommended Dimensions for Ferrule.
   Dual Crimp: Providing Recommended Dimensions for Ferrule and Center Pin.
   Please Advise Single/Dual in Advance to Avoid any Inconvenience.
2. All Metal Materials are in Compliance with RoHS 2 Directive 2011/65/EU Annex III Section 6 Paragraph.
3. Recommended Crimped Hand Tool : for Center Pin P/N - HT-301G2
   for Ferrule P/N - HT-H116N





Recommended Mounting Hole



Recommended Cable Stripping Dimensions



Recommended Crimping Dimensions for Center Pin



Recommended Crimping Dimensions for Ferrule

Finish : [Plating Thickness Unit in Micro Inch(μ)]

1. Nickel Plating Thickness : 80 μ"
2. Gold Plating Thickness : Gold Flash

ITEM	Description	Material	Finish	Part Number	QTY
7	Nut	Brass	Finish 1		
6	Washer	Brass	Finish 1		
5	O-Ring	Si-Rubber	Red		
4	Ferrule	Brass	Finish 1		
3	Pin	Brass	Finish1/2		
2	Insulator	PTFE	None		
1	Body	Brass	Finish 1		

Scale	Abbr.	Date	Rev.
NTS	ST	2013/02/19	B

Tolerances :
.X ±0.2
.XX ±0.1
.XXX ±0.05

All Dimensions in mm (Unless Otherwise Specified)

Customer P/N:

Drawn	Checked	Approved

DWG. NO. QMA-1208d-TGN

RoHS 2

TITLE

QMA Straight Dual Crimp Jack
RG174,188,316;B7805A;URM95 Cable

SCHMID-M