


Technische Daten / Technical Data

Isolierkörper <i>Insulator</i>	Thermoplastischer Kunststoff, nach UL94 V-0 <i>Thermoplastic, rated UL94 V-0</i>
Kontaktmaterial <i>Contact Material</i>	Vierkantstift 0,50mm, Kupferlegierung <i>0.50mm square pin, copper alloy</i>
Kantoberfläche <i>Contact Surface</i>	Lt. Oberflächenoptionen, über Ni (1,3 ... 2,5µm) <i>Acc. to options (see below), over Ni (1.3 ... 2.5µm)</i>
Lötbarkeit <i>Solderability</i>	IEC 60512-12A <i>IEC 60512-12A</i>
Durchgangswiderstand <i>Contact Resistance</i>	< 20mΩ
Isolationswiderstand <i>Insulation Resistance</i>	> 500MΩ
Spannungsfestigkeit <i>Test Voltage</i>	500V _{AC}
Nennspannung <i>Voltage Rating</i>	250V _{AC}
Nennstrom <i>Current Rating</i>	1A
Temperaturbereich <i>Temperature Range</i>	-40°C ... +105°C
Verarbeitung <i>Processing</i>	Wellen- oder Reflow-Lötverfahren <i>Wave or reflow soldering</i>

RoHS Compliant		SCHMID-M	
APPD.	 <small>RCAI F</small>	TOLERANCE	PART NAME
DWG.		ANG. ±	Female Headers 2.00mm Pitch, Right-Angled, Single/Double Row
DATE	UNIT	SIZE.	PART NO.
2013/10	M M	A 4	SM C02 6805 XX DR
	PAGE	REV.	
	1 OF 1	C	