



NOTE:

1.MATERIAL:

- a.HOUSING:THERMOPLASTIC GLASS FIBRE UL94V-0
- b.CONTACT:BRASS
(SURFACE PLATING: Sn100u")

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTNIC VOLTAGE: 750V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -55° C ~ +85° C

<p>RoHS Compliant</p>		<p>SCHMID-M</p>	
<p>APPD.</p>		<p>TOLERANCE</p>	<p>PART NAME</p>
<p>DWG.</p> <p>BRAUN</p>	<p>SCALE</p>	<p>0 ±</p> <p>.00 ±</p> <p>ANG. ±</p>	<p>Battery holder for CR 2032, PCB</p>
<p>DATE</p> <p>2013/05/13</p>	<p>UNIT</p> <p>M M</p>	<p>SIZE.</p> <p>A 4</p>	<p>PART NO.</p> <p>SM C07 0170 02 I</p>
<p>PAGE</p> <p>1 OF 1</p>	<p>REV.</p> <p>A</p>		