



- NOTES:
- 1.0 RATING
 - 1.1 VOLTAGE:10 VAC(rms)
 - 1.2 CURRENT: 5 AMPERES MAX PER CONTACT
 - 1.3 OPERATION TEMPERATURE RANGE:-40°C~+85°C
 - 2.0 ELECTRIC CHARACTERISTIC
 - 2.1 CONTACT RESISTANCE:80mΩ MAX
 - 2.2 INSULATION RESISTANCE:1000MΩ MIN
 - 2.3 DIELECTRIC WITHSTANDING VOLTAGE:500V DC FOR 1 MINUTE
 - 3.0 OPERATION LIFE:5000 CYCLES
 - 4.0 MATERIAL/FINISH SEE TABLE A
 - 4.1 T FLASH CARD SEE TABLE B

TABLE B:

PIN #	DATI	I/O/PP	DATE LINE(BIT 1)
PIN 7	DATO	I/O/PP	DATE LINE(BIT D)
PIN 6	VSS	S	SUPPLY VOLTAGE GROUND
PIN 5	CLK	1	COLCK
PIN 4	VDD	S	SUPPLY VOLTAGE
PIN 3	CMD	PP	COMMAND RESPONSE
PIN 2	CD/DAT 3	I/O/PP	CARD DETECT/DATE LINE BIT 3
PIN 1	DAT 2	I/O/PP	DATE LINE(BIT 2)
PIN NO.	NAME.	TYPE	DESCRIPTION

ITEM	NAME	Q'TY	MATERIAL/FINISH
3	SHELL	1	STAINLESS STEEL
2	CONTACT	8	COPPER ALLOY/CONTACT AREA:GOLD PLATER,SOLDERING AREA:SN PLATER;
1	HOUSING	1	THERMOPLASTIC/UL 94V-0;BLACK

TOLERANCE			
SCALE	UNIT mm		
DRAW Walter	DATE 18.1.2023	TITLE SM C06 0808 SMD	
CHECK Spirk	REV		
		DESCRIPTION microSD, SMT, 8pin	