

FEATURE:



INSULATOR
Glass-Filled P.B.T. is 94V-0 rated
CONTACT
Phosphor Bronze selective gold plating over nickel

SPECIFICATION:

Current Rating : 3 amperes
Contact Resistance : 20 miniohms max.
Operation Temperature : -55°C to +105°C
Voltage Rating : 800 VAC 1 minute
Insulation Resistance : 5000 megaohms min.
Insertion Force : 412 grams max. per pair
Withdrawal Force : 32 grams min. per pair

Dimension

Position	A	B	C	Position	A	B	C
08M*	16.46	13.06	7.62	36M	52.02	48.62	43.18
10M	19.00	15.60	10.16	40M	57.10	53.70	48.26
12M	21.54	18.14	12.70	44M	62.18	58.78	53.34
14M	24.08	20.68	15.24	50M	69.80	66.40	60.96
20M	31.70	28.30	22.86	60M	82.50	79.10	73.66
22M	34.24	30.84	25.40	62M	85.04	81.64	76.20
24M	36.78	33.38	27.94	72M	97.74	94.34	88.90
26M	39.32	35.92	30.48	86M*	115.52	112.12	106.68
30M	44.40	41.00	35.56	100M	133.30	129.90	124.46

TOLERANCE		
SCALE	UNIT mm	
DRAW Green	DATE 14.4.2021	TITLE
CHECK	REV	SM C06 3600 XX SN-4,3mm
		DESCRIPTION
		Edge Card Connector 2,54mm