

PCB Layout Diagram  
Top View

NOTE:

1.MATERIAL:

- a.HOUSING:THERMOPLASTIC GLASS FIBRE UL94V-0
- b.CONTACT:PHOSPHOR WHITE



(SURFACE PLATING: A\*U")

SEE ORDERING INFORMATION

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTNIC VOLTAGE: 750V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -25°C~ +85°C

NO.	PART NAME	Q' TY	MATERIAL	PLATING & COLOR
3	TERMINAL(-)	1	PHOSPHOR BRONZE, T=0.15MM	Gold Plating and Ni Under-Plating
2	TERMINAL(+)	1	PHOSPHOR BRONZE, T=0.15MM	Gold Plating and Ni Under-Plating
1	HOUSING	1	LCP	WHITE

TOLERANCE			
SCALE	UNIT mm		
DRAW Walter	DATE 6.6.2021	TITLE	
CHECK Paul	REV	<b>SM C07 0170 02 U-SMT-2450</b>	
		DESCRIPTION	
		Battery Holder SMT 2450	